

# External Gear Ball Slewing Ring Useing for Slewing Conveyer

With 0.0 Inventory over 10170 full-service stores, our External Gear Ball Slewing Ring Useing for Slewing Conveyer inventory is extensive and our parts are priced right. within 24 N/A Minimum Buy Quantity hours. TIMKEN Manufacturer Name This helps you maximize your productivity by saving time and your hard-earned dollars.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	14.528
EAN	0883450186254
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	V Lock
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Steel
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22219
Seals	Triple Lip Nitrile Rubber
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot

Inch – Metric	Inch
Long Description	4 Bolt Round Flange Cartridge; 3-1/2" Bore; 8.6" Bolt Circle; 6.1" Bolt Spacing; 1 Pi
Other Features	Double Row   Double Nut
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Weight / LBS	32
D	4.49 Inch   114.046 Millimeter
Cartridge Pilot Diameter	7.375 Inch   187.32 Millimeter
Bolt Spacing	6.1 Inch   154.9 Millimeter
d	3.5 Inch   88.9 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Nominal Bolt Circle Diameter Round	8.6 Inch   218.4 Millimeter