

FAG 22309-E1-T41A spherical roller bearings

How 10x3x4 Size (mm) do you find the FAG 22309-E1-T41A spherical roller bearings specification? Manufacturers Online Free check 10 Bore Diameter (mm)

Size (mm)	10x3x4
Bore Diameter (mm)	10
Outer Diameter (mm)	3
Width (mm)	4
d	3 mm
D	10 mm
B	4 mm
d1	5.2 mm
D2	8.2 mm
r1,2 – min.	0.15 mm
da – min.	4.2 mm
da – max.	5.1 mm
Da – max.	8.8 mm
ra – max.	0.1 mm
Basic dynamic load rating – C	0.54 kN
Basic static load rating – C0	0.18 kN
Fatigue load limit – Pu	0.007 kN
Reference speed	130000 r/min
Limiting speed	60000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	7.5
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.004
EAN	7316577094933
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	3MM Bore; 10MM Outside Diameter; 4MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 IS
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	623-2Z
Weight / LBS	0.01
Outer Race Width	0.157 Inch 4 Millimeter
Bore	0.118 Inch 3 Millimeter
Outside Diameter	0.394 Inch 10 Millimeter
bore diameter:	3 mm
static load capacity:	0.18 kN
outside diameter:	10 mm

precision rating:	Not Rated
overall width:	4 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
outer ring width:	4 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.1 mm
internal clearance:	C0
maximum rpm:	60000 RPM
dynamic load capacity:	0.54 kN
series:	62
d1 ≈	5.2 mm
D2 ≈	8.2 mm
r1,2 min.	0.15 mm
da min.	4.2 mm
da max.	5.1 mm
Da max.	8.8 mm
ra max.	0.1 mm
Basic dynamic load rating C	0.54 kN
Basic static load rating C0	0.18 kN
Fatigue load limit Pu	0.007 kN
Calculation factor kr	0.025
Calculation factor f0	7.5
Mass bearing	0.0015 kg