

FAG 23138-E1A-K-M + AH3138G spherical roller bearings

FAG 23138-E1A-K-M + AH3138G spherical roller bearings with easy-to-use parts 60 Bore Diameter (mm) graphics, giving you the 60x110x22 Size (mm) ability to check parts availability, pricing, examine remanufactured 110 Outer Diameter (mm) options.

Size (mm)	60x110x22
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Width (mm)	22
d	60 mm
D	110 mm
B	22 mm
C	22 mm
rn	0,5 mm
r min.	1,5 mm
da min.	68 mm
da max	75 mm
Da max.	102 mm
ra max.	1,5 mm
Weight	0,783 Kg
Basic dynamic load rating (C)	52,5 kN
Basic static load rating (C0)	36 kN
(Grease) Lubrication Speed	6 000 r/min
Inventory	4.0
Manufacturer Name	NTN

Minimum Buy Quantity	N/A
Weight / Kilogram	0.78
EAN	4547359004885
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6212ZZCM/5K
Weight / LBS	1.71
Outside Diameter	4.331 Inch 110 Millimeter
Bore	2.362 Inch 60 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter
bore diameter:	60 mm
precision rating:	ISO Class 0
outside diameter:	110 mm
finish/coating:	Uncoated

overall width:	22 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	22 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	22 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	6000 rpm
internal clearance:	CN
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	7000 RPM
dynamic load capacity:	52500 N
series:	62
static load capacity:	36000 N
manufacturer product page:	Click here