

FAG 232/710-B-K-MB spherical roller bearings

YOU'LL 138.113 mm da FIND AN EXTENSIVE SELECTION OF FAG 232/710-B-K-MB spherical roller bearings FOR 289.999 mm Da SALE.

da	138.113 mm
Da	289.999 mm
Ca	89.789 mm
A1	158.75 mm
A2	225.425 mm
S	4.763 mm
ba	70.644 mm
H	338.137 mm
H1	169.875 mm
H2	66.675 mm
L	558.8 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	51.594 mm
Housing	SSAFS 532
Bearing	22232 CCK/W33
Adapter sleeve assembly	SNW 32×5.7/16
Stabilizing ring	SR-32-0
Labyrinth ring	2 x LOR 130
PosiTrac Plus contact element	2 x B10724-130

End plug (suffix Y)	EPR 16
Max. speed for PosiTrac Plus seal	1050 r/min
P60°	345 kN
P90°	207 kN
P120°	133 kN
P150°	120 kN
P180°	145 kN
Pa	38.5 kN
Mass pillow block	132 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	793.8 g