

FAG 23284-B-K-MB+H3284 spherical roller bearings

High Quality FAG 23284-B-K-MB+H3284 spherical roller bearings. Competitive 20 mm d Pricing. Accept Small Order. Easy and Fast 52 mm D Shipping. 15 mm B

| | |
|---|------------|
| d | 20 mm |
| D | 52 mm |
| B | 15 mm |
| rs min | 1.1 mm |
| Radial clearance class | C3 |
| Mass | 0.14 kg |
| Dynamic load, C | 15.9 kN |
| Static load, C ₀ | 7.9 kN |
| Fatigue limit load, C _u | 0.36 kN |
| f ₀ | 12.4 |
| N _{lim} (grease) | 14,000 rpm |
| Min operating temperature, T _{min} | -35 °C |
| Max operating temperature, T _{max} | 180 °C |
| Characteristic cage frequency, FTF | 0.37 Hz |
| Characteristic rolling element frequency, BSF | 3.52 Hz |
| Characteristic outer ring frequency, BPF ₀ | 2.57 Hz |
| Characteristic inner ring frequency, BRF ₀ | 4.43 Hz |
| da min | 26.5 mm |
| Da max | 45.5 mm |
| ra max | 1 mm |

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.144 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO |
| Other Features | Deep Groove |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 0.32 |
| Bore | 0.787 Inch 20 Millimeter |
| Outside Diameter | 2.047 Inch 52 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 0.591 Inch 15 Millimeter |