

# FAG 23284-B-K-MB+H3284 spherical roller bearings

High Quality FAG 23284-B-K-MB+H3284 spherical roller bearings. Competitive 20 mm d Pricing. Accept Small Order. Easy and Fast 52 mm D Shipping. 15 mm B

d	20 mm
D	52 mm
B	15 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.14 kg
Dynamic load, C	15.9 kN
Static load, C0	7.9 kN
Fatigue limit load, Cu	0.36 kN
f0	12.4
Nlim (grease)	14,000 rpm
Min operating temperature, Tmin	-35 °C
Max operating temperature, Tmax	180 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.52 Hz
Characteristic outer ring frequency, BPF0	2.57 Hz
Characteristic inner ring frequency, BRFI	4.43 Hz
da min	26.5 mm
Da max	45.5 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.144
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.32
Bore	0.787 Inch   20 Millimeter
Outside Diameter	2.047 Inch   52 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.591 Inch   15 Millimeter