FAG 23992-B-K-MB spherical roller bearings

Find the 0.0 Inventory discount FAG 23992-B-K-MB spherical roller bearings online you need . We offer \dots If you check out our large selection of FAG 23992-B-K-MB spherical roller bearings once .

| Inventory | 0.0 |
|---------------------------|------------------------------------------------------------------------------|
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 10.64 |
| EAN | 0013992050717 |
| Product Group | B04144 |
| Number of Mounting Holes | 2 |
| Mounting Method | Clamp Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 16 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | LSE204BX |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch — Metric | Inch |
| Other Features | Single Row Light Duty With Support Wide Inner Ring Axial Float |
| UNSPSC | 31171511 |

| Harmonized Tariff Code | 8483.20.40.80 |
|-------------------------------|-----------------------------------------|
| Noun | Bearing |
| Keyword String | Pillow Block |
| Weight / LBS | 23.43 |
| В | 3.15 Inch 80 Millimeter |
| D | 2.362 Inch 60 Millimeter |
| d | 2.25 Inch 57.15 Millimeter |
| Bolt Spacing Minimum | 0 Inch OMillimeter |
| Nominal Bolt Center to Center | 9.2 Inch 234 Millimeter |
| Bolt Spacing Maximum | 0 Inch OMillimeter |
| Actual Bolt Center to Center | 9.2 Inch 234Millimeter |
| Shaft Size | 2.25 in |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Expansion Type |
| Support Type | Two-Bolt Plummer Block |
| Series Type | Light Series |
| Pillow/Plummer Block Style | Split Cylindrical Housed Unit - SAFQ |
| Bolt Size | 2 x 5/8 |
| Bearing UPC | 013992025845 |
| Dimension H | 3-1/4 in |
| Dimension H2 | 7.2 in |
| Dimension J1 | 9-5/8 in |
| Dimension J2 | 8-5/8 in |
| Dimension L | 11-1/8 in |
| Dimension M | 3-1/8 in |
| Housing Width | 4.1 in |
| Cr — Dynamic Load Rating | 23118 lbf |

| Cor — Static Load Rating | 25848 lbf |
|--------------------------|---------------------------------------------------|
| Maximum Speed | 3940 rpm |
| Note | This product line was formerly known as "Revolvo" |