

FAG 240/750-B-K30-MB + AH240/750-H spherical roller bearings

Shop 28 mm B FAG 240/750-B-K30-MB + AH240/750-H spherical roller bearings huge online discount inventory. and Import machinery parts your car needs with Free Shipping and Free 85 mm d Extended Warranty.

d	85 mm
D	150 mm
B	28 mm
E	133.8 mm
F	101.8 mm
d1	108.2 mm
rs min	2 mm
r1s min	2 mm
Radial clearance class	C3
Mass (without HJ ring)	1.94 kg
Dynamic load, C	120 kN
Static load, C0	140 kN
Fatigue limit load, Cu	16.3 kN
Nlim (oil)	5,300 rpm
Nlim (grease)	4,500 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz

Characteristic rolling element frequency, BSF	7.23 Hz
Characteristic outer ring frequency, BPF0	6.91 Hz
Characteristic inner ring frequency, BPFI	9.09 Hz
da min	94 mm
da max	99 mm
dc min	110 mm
Da max	141 mm
ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.93
EAN	4547359118285
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric

Other Features	1 Rib Inner Ring 2 Rib Outer Ring Cage On Outer Ring ID
Long Description	85MM Bore; Straight Bore Profile; 150MM Outside Diameter; 28MM Width; Steel Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NJ217C3
Weight / LBS	4.261
Outside Diameter	5.906 Inch 150 Millimeter
Bore	3.346 Inch 85 Millimeter
Width	1.102 Inch 28 Millimeter
bore diameter:	85 mm
precision rating:	ISO Class 0
outside diameter:	150 mm
maximum rpm:	5300 rpm
overall width:	28 mm
bearing material:	Hardened Alloy Steel
flanges:	(2) Outer Ring, (1) Inner Ring
cage material:	Pressed Steel
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3

outer ring width:	28 mm
ring separation:	Non-Separable
fillet radius:	2 mm
operating temperature range:	-40 to 120 °C
series:	NJ
dynamic load capacity:	120000 N
manufacturer product page:	Click here
static load capacity:	140000 N