

FAG 24084-B-K30-MB spherical roller bearings

170 Million used FAG 24084-B-K30-MB spherical roller bearings 259.999 mm Da instantly searchable. Shop our large selection of parts based on brand, price, description, 86.614 mm Ca and location. 152.4 mm da Order the with stock ...

da	152.4 mm
Da	259.999 mm
Ca	86.614 mm
A1	149.225 mm
A2	193.675 mm
ba	64.294 mm
H	298.45 mm
H1	152.4 mm
H2	60.325 mm
J min.	406.4 mm
J max.	434.975 mm
J1	85.725 mm
L	511.175 mm
N1	28.575 mm
R1	87.313 mm
R2	38.1 mm
RG	3/4 NPT
PG	1/4 NPT
h	44.45 mm
Housing	SAFS 034 KA
Bearing	23034 CCK/W33

Adapter sleeve assembly	SNW 3034×6
Stabilizing ring	2 x SR-0-24
Labyrinth ring	2 x LOR 141
PosiTrac Plus contact element	2 x B10724-140
End plug (suffix Y)	EPR 18
Max. speed for PosiTrac Plus seal	950 r/min
P60°	301 kN
P90°	180 kN
P120°	116 kN
P150°	105 kN
P180°	127 kN
Pa	34 kN
Mass pillow block	87.5 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	481.95 g