

FAG 32306-A tapered roller bearings

Enjoy High 55×56.67×60 Size (mm) Margins on 56,67 Outer Diameter (mm) Competitive Pricing.Great Wholesale Products at Low Costs.

Size (mm)	55×56.67×60
Bore Diameter (mm)	55
Outer Diameter (mm)	56,67
Width (mm)	60
d	56.67 mm
A	60 mm
A1	40 mm
A5	34 mm
B1	49 mm
H	27.5 mm
H1	63.5 mm
H2	24 mm
J	171.5 mm
J – max.	181 mm
J – min.	162 mm
L	219 mm
N1	18 mm
s1	29 mm
J6	201 mm
J7	21 mm
N4	4 mm
DN	6.5 mm

SWN	7 mm
GN – 1/4-28 SAE-LT	1/428 SAELT
RG – 1/4-28 UNF	1/428 UNF
R1	4.5 mm
Rα	45 °
Basic dynamic load rating – C	43.6 kN
Basic static load rating – C0	29 kN
Fatigue load limit – Pu	1.2 kN
Limiting speed	3600 r/min
Weight	3.35 kg
Hexagonal key size for grub screw – H	3 mm
Recommended tightening torque for grub screw	7.4 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
UNSPSC	31171511
Weight / Kilogram	0
EAN	7316574719020
Product Group	M06110
Housing material	Cast iron
J max.	181 mm
J min.	162 mm
N	27.5 mm
RG	1/4-28 UNF
Rα	45 °
GN	1/4-28 SAE-LT
Basic dynamic load rating C	43.6 kN
Basic static load rating C0	29 kN
Fatigue load limit Pu	1.25 kN

Mass bearing unit	3.35 kg
Thread grub screw G2	M6
Hexagonal key size for grub screw N	3 mm
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Housing	SY 511 M
Bearing	YSP 211 SB-2F
End cover	ECY 211