

FAG 33014-N11CA tapered roller bearings

How do you find 25,4 Bore Diameter (mm) the 25,4 mm d 19.8 mm s1 FAG 33014-N11CA tapered roller bearings specification? Manufacturers Online Free check

Bore Diameter (mm)	25,4
d	25,4 mm
s1	19.8 mm
A	32 mm
A1	23 mm
B	34,1 mm
G	10 mm
H	56 mm
H1	28.4 mm
H2	3.2 mm
J	86 mm
L	108 mm
N	11,2 mm
Weight	0,27 Kg
Basic dynamic load rating (C)	14 kN
Basic static load rating (C0)	7,8 kN
Housing material	Pressed steel
B4	5 mm
Basic dynamic load rating C	14 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Permissible radial housing load max.	1.8 kN

Limiting speed	4300 r/min
Mass bearing unit	0.29 kg
Thread grub screw G2	1/4-28 UNF
Hexagonal key size for grub screw N	3.175 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	P 52
Bearing	YAR 205-100-2RF