

FAG 53226 thrust ball bearings

FAG 53226 thrust ball bearings, Units and Housings CAD 25 mm d models , Manufacturing Service . 15 mm B Get Your Free.

d	25 mm
D	52 mm
B	15 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.13 kg
Dynamic load, C	14 kN
Static load, C0	7.85 kN
Fatigue limit load, Cu	0.36 kN
f0	13.9
Nlim (grease)	13,000 rpm
Min operating temperature, Tmin	-30 °C
Max operating temperature, Tmax	175 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.71 Hz
Characteristic outer ring frequency, BPF0	3.58 Hz
Characteristic inner ring frequency, BRFI	5.42 Hz
da min	30 mm
Da max	47 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	25MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Chevron SRI2 Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.282
Inner Race Width	0 Inch 0 Millimeter
Bore	0.984 Inch 25 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter