

# FAG 546065 deep groove ball bearings

Question FAG 546065 deep groove ball bearings ? Find 340x160x114 Size (mm) what you need faster by entering your information 340 Bore Diameter (mm) .

|                               |             |
|-------------------------------|-------------|
| Size (mm)                     | 340x160x114 |
| Bore Diameter (mm)            | 340         |
| Outer Diameter (mm)           | 160         |
| Width (mm)                    | 114         |
| d                             | 160 mm      |
| D                             | 340 mm      |
| B                             | 114 mm      |
| d1                            | 221 mm      |
| D1                            | 286 mm      |
| F                             | 204 mm      |
| r1,2 – min.                   | 4 mm        |
| r3,4 – min.                   | 4 mm        |
| s                             | 11 mm       |
| da – min.                     | 177 mm      |
| da – max.                     | 199 mm      |
| db – min.                     | 225 mm      |
| Da – max.                     | 321.9 mm    |
| ra – max.                     | 3 mm        |
| Basic dynamic load rating – C | 1250 kN     |
| Basic static load rating – C0 | 1730 kN     |
| Fatigue load limit – Pu       | 173 kN      |
| Reference speed               | 1800 r/min  |

|                             |               |
|-----------------------------|---------------|
| Limiting speed              | 3600 r/min    |
| Calculation factor – kr     | 0.38          |
| Inventory                   | 0.0           |
| Manufacturer Name           | SKF           |
| Minimum Buy Quantity        | N/A           |
| UNSPSC                      | 31171547      |
| Weight / Kilogram           | 0             |
| EAN                         | 7316574923533 |
| Product Group               | B04144        |
| d1 ≈                        | 221 mm        |
| D1 ≈                        | 286 mm        |
| r1,2 min.                   | 4 mm          |
| r3,4 min.                   | 4 mm          |
| s max.                      | 11 mm         |
| da min.                     | 177 mm        |
| da max.                     | 199 mm        |
| db min.                     | 225 mm        |
| Da max.                     | 321.9 mm      |
| ra max.                     | 3 mm          |
| Basic dynamic load rating C | 1250 kN       |
| Basic static load rating C0 | 1730 kN       |
| Fatigue load limit Pu       | 173 kN        |
| Calculation factor kr       | 0.38          |
| Limiting value e            | 0.3           |
| Axial load factor Y         | 0.4           |
| Mass bearing                | 50.7 kg       |