

FAG 6204-2RSR deep groove ball bearings

LET OUR FAG 6204-2RSR deep groove ball bearings EXPERTS 17 Bore Diameter (mm) GET YOU THE PARTS YOU 17x30x7 Size (mm) 30 Outer Diameter (mm) NEED.

Size (mm)	17x30x7
Bore Diameter (mm)	17
Outer Diameter (mm)	30
Width (mm)	7
d	17 mm
D	30 mm
B	7 mm
C	7 mm
a	1.3 mm
b	0.95 mm
r min.	0.3 mm
r1 min.	0.3 mm
D1	28.7 mm
Weight	0.019 Kg
Basic dynamic load rating (C)	4,6 kN
Basic static load rating (C0)	2,55 kN
(Grease) Lubrication Speed	24000 r/min
Bore Type	Cylindrical Bore
Enclosure	Open
Configuration	Single Row
Bore Size	17 mm
Outside Diameter	30 mm

Width	7 mm
Fillet Radius/Chamfer	0.3 mm
r1	0.3 mm
Groove Width	1 mm
Groove Diameter	28.7 mm
a (max)	1.3 mm
Dynamic Load Rating	4,600 N
Static Load Rating	2,550 N
Limiting Speed – Grease	24,000 rpm
Limiting Speed – Oil	29,000 rpm
Factor fo	14.7
Radial Clearance	0.003 to 0.018 mm
da (min)	19 mm
Da (max)	28 mm
Dx (min)	33.5 mm
ra (max)	0.3 mm
Cy (max)	1.8 mm