

FAG B71940-C-T-P4S angular contact ball bearings

Manufacturers of all are represented 75x130x25 Size (mm) in our partial list of clients. Contact Gary for a complete FAG B71940-C-T-P4S angular contact ball bearings list of clients 75,000 Bore Diameter (mm) 130,000 Outer Diameter (mm) and projects.

| | |
|------------------------------------|------------|
| Size (mm) | 75x130x25 |
| Bore Diameter (mm) | 75,000 |
| Outer Diameter (mm) | 130,000 |
| Width (mm) | 25,000 |
| d | 75,000 mm |
| D | 130,000 mm |
| B | 25,000 mm |
| C | 25,000 mm |
| rs min | 1.5 mm |
| Radial clearance class | CN |
| Mass | 1.18 kg |
| Dynamic load, C | 66 kN |
| Static load, C0 | 49.5 kN |
| Fatigue limit load, Cu | 2.21 kN |
| f0 | 14.7 |
| Nlim (grease) | 3,200 rpm |
| Min operating temperature, Tmin | -25 °C |
| Max operating temperature, Tmax | 110 °C |
| Characteristic cage frequency, FTF | 0.42 Hz |

| | |
|---|-----------------|
| Characteristic rolling element frequency, BSF | 5.76 Hz |
| Characteristic outer ring frequency, BPF0 | 4.57 Hz |
| Characteristic inner ring frequency, BPFI | 6.43 Hz |
| da min | 83 mm |
| da max | 90.5 mm |
| Da max | 122 mm |
| ra max | 1.5 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.15 |
| EAN | 4547359370935 |
| Product Group | B00308 |
| Enclosure | 1 Seal |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |

| | |
|------------------------|---|
| Long Description | 75MM Bore; 130MM Outside Diameter; 25MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 2.54 |
| Outer Race Width | 0.984 Inch 25 Millimeter |
| Outside Diameter | 5.118 Inch 130 Millimeter |
| Bore | 2.953 Inch 75 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |