

# FAG F-804462.ZL-K-C3 cylindrical roller bearings

What is FAG F-804462.ZL-K-C3 cylindrical roller bearings in mechanical engineering? 2.0 Inventory Manufacturing Service . Upload your CAD file for an instant.

|                           |   |
|---------------------------|---|
| Inventory                 | 2.0   |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.18  |
| EAN                       | 0782475247356   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 7/16 Inch   |
| Relubricatable            | Yes   |
| Insert Part Number        | INS-SC-104S   |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Square Flange Block;<br>1-1/4" Bore; 4.7" Bolt Circle;<br>3-1/4" Bolt Spacing; 1 Pie |

|                                       |   |
|---------------------------------------|---|
| Other Features                        | Single Row   Normal Duty  <br>Wide Inner Race |
| UNSPSC                                | 31171501                                      |
| Harmonized Tariff Code                | 8483.20.40.40                                 |
| Noun                                  | Bearing                                       |
| Keyword String                        | Flanged                                       |
| Manufacturer Item Number              | F4B-SC-104S                                   |
| Manufacturer Internal Number          | 123173  |
| Weight / LBS                          | 2.6   |
| Nominal Bolt Circle Diameter<br>Round | 4.7 Inch   120 Millimeter                     |
| D                                     | 1.391 Inch   35.331 Millimeter                |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                         |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                         |
| Bolt Spacing                          | 3.25 Inch   82.55 Millimeter                  |
| d                                     | 1.25 Inch   31.75 Millimeter                  |