

FAG HCS7003-E-T-P4S angular contact ball bearings

YOU'LL 35 mm D FIND AN 15 mm d EXTENSIVE SELECTION OF FAG HCS7003-E-T-P4S angular contact ball bearings FOR SALE.

d	15 mm
D	35 mm
B	11 mm
rs min	0.6 mm
Radial clearance class	C3
Mass	0.04 kg
Dynamic load, C	7.75 kN
Static load, C0	3.6 kN
Fatigue limit load, Cu	0.16 kN
f0	12.7
Nlim (grease)	15,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.68 Hz
Characteristic outer ring frequency, BPF0	2.61 Hz
Characteristic inner ring frequency, BRFI	4.39 Hz
da min	19 mm
da max	20 mm
Da max	31 mm

ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0692314625934
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Weight / LBS	0.099
Outer Race Width	0.433 Inch 11 Millimeter
Bore	0.591 Inch 15 Millimeter
Outside Diameter	1.378 Inch 35 Millimeter
Inner Race Width	0 Inch 0 Millimeter