

FAG HSS71918-E-T-P4S angular contact ball bearings

FAG HSS71918-E-T-P4S angular contact ball bearings SEARCH – Whether it's agriculture or construction 52 mm D equipment your working on, Has the you need. 20 mm d 21 mm B

d	20 mm
D	52 mm
B	21 mm
E	45.5 mm
F	27.5 mm
d1	31.1 mm
rs min	1.1 mm
rls min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.24 kg
Dynamic load, C	42 kN
Static load, C0	39 kN
Fatigue limit load, Cu	4.75 kN
Nlim (oil)	14,000 rpm
Nlim (grease)	12,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	3.81 Hz
Characteristic outer ring frequency, BPF0	3.77 Hz
Characteristic inner ring frequency, BPF1	6.23 Hz
da min	26.5 mm

da max	27 mm
dc min	33 mm
Da max	45.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.242
Product Group	B04144