

FAG KJL69349-JL69310 tapered roller bearings

FAG KJL69349-JL69310 tapered roller bearings Industries and Applications ? We sell OH 30/530 H Adapter sleeve discount online as well as cheap machinery parts. C 30/530 K Bearing (basic designation)

Bearing (basic designation)	C 30/530 K
Adapter sleeve	OH 30/530 H
Locating ring	2 x FRB 31.5/780
da	500 mm
Ca	248 mm
Da	780 mm
A	465 mm
A1	440 mm
A2	465 mm
H	920 mm
H1	460 mm
H2	155 mm
J	1110 mm
J1	260 mm
L	1330 mm
N	70 mm
N1	56 mm
s	35 mm
J6	1210 mm
N4 max.	40 mm
Oil seal	2 x TSD 30/530 U

P0°	8800 kN
P55°	11200 kN
P90°	5400 kN
P120°	4000 kN
P150°	3500 kN
P180°	4400 kN
Q120°	5800 kN
Q150°	3350 kN
Q180°	2900 kN
Mass housing	941 kg
Cap bolt, size	M 42×320
Cap bolt, rec. tightening torque	850 N·m
Appropriate attachment bolt, size G	48 mm
Appropriate attachment bolt, rec. tightening torque	5450 N·m
Eye bolt, size	2 x M 48
Oil level, min.	110 mm
Oil level, max.	134 mm