

FAG NN3068-AS-K-M-SP cylindrical roller bearings

Request A Quote 260x120x55 Size (mm) For Your Special FAG NN3068-AS-K-M-SP cylindrical roller bearings Needs Today! Free Quotes. ISO 9001 certified.

Size (mm)	260x120x55
Bore Diameter (mm)	260
Outer Diameter (mm)	120
Width (mm)	55
d	120 mm
D	260 mm
B	55 mm
d1	168 mm
D1	217.8 mm
F	154 mm
r1,2 – min.	3 mm
r3,4 – min.	3 mm
s	3.7 mm
da – min.	134 mm
da – max.	150 mm
db – min.	171 mm
Da – max.	244.8 mm
ra – max.	2.5 mm
Basic dynamic load rating – C	610 kN
Basic static load rating – C0	620 kN
Fatigue load limit – Pu	69.5 kN
Reference speed	2800 r/min

Limiting speed	3200 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	13.482
EAN	7316577042873
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	120MM Bore; Straight Bore Profile; 260MM Outside Diameter; 55MM Width; Steel Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00

Noun	Bearing
Manufacturer Item Number	NJ 324 ECJ
Weight / LBS	29.696
Bore	4.724 Inch 120 Millimeter
Width	2.165 Inch 55 Millimeter
Outside Diameter	10.236 Inch 260 Millimeter
d1 ≈	168 mm
D1 ≈	217.8 mm
r1,2 min.	3 mm
r3,4 min.	3 mm
s max.	3.7 mm
da min.	134 mm
da max.	150 mm
db min.	171 mm
Da max.	244.8 mm
ra max.	2.5 mm
Basic dynamic load rating C	610 kN
Basic static load rating C0	620 kN
Fatigue load limit Pu	69.5 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	13.3 kg
Angle ring	HJ 324 EC