

FAG NU2203-E-TVP2 cylindrical roller bearings

Request A Quote For Your Special FAG NU2203-E-TVP2 cylindrical roller bearings Needs Today! Free 61.913 mm da Quotes. ISO 9001 certified.

da	61.913 mm
Da	130 mm
Ca	37.008 mm
A1	79.375 mm
A2	118.666 mm
ba	30.163 mm
H	157.559 mm
H1	82.55 mm
H2	28.575 mm
J min.	219.075 mm
J max.	244.475 mm
J1	47.625 mm
L	285.75 mm
N1	15.875 mm
R1	46.038 mm
R2	21.431 mm
RG	1/4 NPT
PG	1/8 NPT
h	31.75 mm
Housing	FSAF 515
Bearing	1215 K
Adapter sleeve assembly	SNW 15×2.7/16

Stabilizing ring	2 x SR-15-0
Labyrinth ring	2 x LOR 37
End plug (suffix Y)	EPR 7
Bearing limiting speed	6700 r/min
P60°	54.3 kN
P90°	32.5 kN
P120°	20 kN
P150°	18.2 kN
P180°	22.2 kN
Pa	5.65 kN
Mass pillow block	12.7 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	81.3 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	136.08 g