

FAG NUP303-E-TVP2 cylindrical roller bearings

Online shopping FAG NUP303-E-TVP2 cylindrical roller bearings from a great selection at 85.725 mm dc Store. ... 90 mm da 104.775 mm db Accessories.

da	90 mm
db	104.775 mm
dc	85.725 mm
Da	160 mm
Ca	49.809 mm
A1	98.425 mm
A2	149.225 mm
ba	34.925 mm
H	192.484 mm
H1	101.6 mm
H2	41.275 mm
J min.	260.35 mm
J max.	298.45 mm
L	349.25 mm
N1	22.225 mm
R1	60.325 mm
R2	27.781 mm
RG	3/8 NPT
PG	1/8 NPT
h	38.1 mm
Housing	SAF 218
Bearing	1218

Lock nut	AN 18
Lock washer	W 18
Stabilizing ring	2 x SR-1518
Labyrinth ring (db shaft position)	LOR 112
Labyrinth ring (dc shaft position)	LOR 191
End plug (suffix Y)	EPR 14
Bearing limiting speed	3800 r/min
P60°	121 kN
P90°	72.5 kN
P120°	45.4 kN
P150°	40.5 kN
P180°	49.8 kN
Pa	32 kN
Mass pillow block	20 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	286.33 g