

FBJ 22226 spherical roller bearings

FBJ 22226 spherical roller bearings Product Brochures , 120 Bore Diameter (mm) Manufacturing Service 120x155x25 Size (mm) . Get Your Free.

Size (mm)	120x155x25
Bore Diameter (mm)	120
Outer Diameter (mm)	155
Width (mm)	25
d	120 mm
D	155 mm
T	25 mm
d1	155 mm
r min.	1 mm
D1	122 mm
da min.	141 mm
Da max.	134 mm
ra max.	1 mm
Weight	1,12 Kg
Basic dynamic load rating (C)	90 kN
Basic static load rating (C0)	310 kN
(Grease) Lubrication Speed	1600 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.163
EAN	0029176029004

Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Flat Seat
Long Description	120MM Bore 1; 122MM Bore 2; 155MM Outside Diameter; 25MM Height; Ball Bearing; Single Direction; Not
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	51124
Weight / LBS	2.46918
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Outside Diameter	6.102 Inch 155 Millimeter
Bore 2	4.803 Inch 122 Millimeter
Bore 1	4.724 Inch 120 Millimeter
Height	0.984 Inch 25 Millimeter
bore diameter:	120 mm
static load capacity:	69000 lbf
outside diameter:	155 mm
dynamic load capacity:	20200 lbf

overall width:	25 mm
operating temperature range:	Maximum of +120 °C
thrust bearing type:	Single-Direction
maximum rpm:	2400 rpm
outside diameter design:	Straight
cage material:	Steel Cage
separable or banded:	Separable
fillet radius:	1 mm
race type:	Flat
series:	51100
precision rating:	ABEC1, P0
SRI	6.85
hidYobi	51124
LangID	1
D_	155
SREX	0.05
C	90
B_	25
hidTable	ecat_NSSDTB
Oil rpm	2400
SRE	6.85
mass	1.12
GRS rpm	1600
ra	1
SRIX	0.05
D_a	134
SRIN	0
C0	310
SREN	0

D_1	122
Prod_Type3	TB_SD_WFS
da	141
DA_	12.7
Z_	31
yobi	51124
SDM_	137.5
r	1
T_	25
KBRG	5111