

# FBJ 23038 spherical roller bearings

Various types and sizes to 0.0 Inventory accommodate your FBJ 23038 spherical roller bearings requirements.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	30.87
EAN	7316576668456
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Shaft Mount
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22222 E
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Metric
Other Features	Double Row   Heavy Duty
Long Description	2 Bolt Pillow Block; 110MM Bore; 125.425MM Base to Center Height; Shaft Mount Mount; Spherical Rolle

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 22222
Weight / LBS	68
Actual Bolt Center to Center	0 Inch   0Millimeter
Bolt Spacing Minimum	12.625 Inch   320.675Millimeter
Nominal Bolt Center to Center	13.6 Inch   344.5 Millimeter
B	4.938 Inch   125.425 Millimeter
Bolt Spacing Maximum	14.5 Inch   368.3Millimeter
d	4.331 Inch   110 Millimeter
D	6.5 Inch   165.1 Millimeter
da	110 mm
db	123.825 mm
dc	106.362 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	165.1 mm
S	4.763 mm
ba	50.006 mm
H	239.316 mm
H1	125.425 mm
H2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm

L	419.1 mm
N1	22.225 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SAF 222
Bearing	22222 E
Lock nut	AN 22
Lock washer	W 22
Stabilizing ring	SR-22-19
Labyrinth ring (db shaft position)	LOR 121
Labyrinth ring (dc shaft position)	LOR 113
End plug (suffix Y)	EPR 14
Bearing limiting speed	4000 r/min
P60°	149 kN
P90°	89 kN
P120°	55.6 kN
P150°	50.7 kN
P180°	60.9 kN
Pa	39.6 kN
Mass pillow block	30.7 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5

Appropriate attachment bolt size G	0.75 in
Initial grease fill	481.95 g