

FBJ 32009 tapered roller bearings

With over 10170 full-service stores, our FBJ 32009 tapered roller bearings inventory 37 Outer Diameter (mm) is extensive and our parts are priced right. within 24 hours. This helps you 25x37x30 Size (mm) maximize your 25 Bore Diameter (mm) productivity by saving time and your hard-earned dollars.

Size (mm)	25x37x30
Bore Diameter (mm)	25
Outer Diameter (mm)	37
Width (mm)	30
Fw	25 mm
D	37 mm
C – 30 mm / Tolerance: -0,25	30 mm / Tolerance: 0,25
C1 – 11 mm / Tolerance: -0,2	11 mm / Tolerance: 0,2
C2	9,5 mm
D2 max	43,2 mm
da	37,7 mm
dw	25 mm / Tolerance: E8
ra max	0,6 mm
rmin	0,6 mm
m	125 g / Weight
Cr	21300 N / Dynamic load rating (radial)
C0r	30500 N / Static load rating (radial)

Ca	33500 N / Dynamic load rating (axial)
C0a	76000 N / Static load rating (axial)
Cur	5300 N / Fatigue limit load, radial
Cua	7100 N / Fatigue limit load, axial
nG	8500 1/min / Limiting speed
nB	3400 1/min / Reference speed
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.15
EAN	4012802664911
Product Group	B00234
Rolling Element	Combination – Needle Roller and Thrust Roller Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Other Features	With Grease Retaining Cap
Long Description	25MM Bore 1; 25MM Bore 2; 37MM Outside Diameter; 30MM Height; Combination – Needle Roller and Thrust
Inch – Metric	Metric

UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.80
Noun	Bearing
Keyword String	Combination
Manufacturer Item Number	NKXR25Z
Weight / LBS	0.265
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Height	1.181 Inch 30 Millimeter
Bore 1	0.984 Inch 25 Millimeter
Outside Diameter	1.457 Inch 37 Millimeter
Bore 2	0.984 Inch 25 Millimeter