

FBJ GEG160ES plain bearings

FBJ GEG160ES plain bearings 88.9 mm da Needs Analysis , 215.001 mm Da Manufacturing Service 82.804 mm Ca . Get Your Free.

da	88.9 mm
Da	215.001 mm
Ca	82.804 mm
A1	120.65 mm
A2	254 mm
S	4.763 mm
ba	57.944 mm
H	258.762 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	51.594 mm
Housing	SAF 620
Bearing	22320 EK
Adapter sleeve assembly	SNW 120×3.1/2

Stabilizing ring	SR-24-20
Taconite seal	TER 103
End plug (suffix Y)	EPR 12
Max. speed for Taconite seal	900 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	21.8 kN
Mass pillow block	51.3 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g