

FBJ JHM911244/JHM911211 tapered roller bearings

High Quality FBJ JHM911244/JHM911211 tapered roller bearings. Competitive Pricing. Accept Small Order. 85 Outer Diameter (mm) Easy 180x85x41 Size (mm) and Fast Shipping.

Size (mm)	180x85x41
Bore Diameter (mm)	180
Outer Diameter (mm)	85
Width (mm)	41
d	85 mm
D	180 mm
B	41 mm
d1	114.55 mm
D2	155.4 mm
r1,2 – min.	3 mm
da – min.	99 mm
da – max.	114.9 mm
Da – max.	166 mm
ra – max.	2.5 mm
Basic dynamic load rating – C	140 kN
Basic static load rating – C0	96.5 kN
Fatigue load limit – Pu	3.6 kN
Reference speed	8000 r/min
Limiting speed	5000 r/min
Calculation factor – kr	0.03
Calculation factor – f0	13
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	4.3
EAN	7316577098931
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	85MM Bore; 180MM Outside Diameter; 41MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6317-Z
Weight / LBS	9.48
Bore	3.346 Inch 85 Millimeter
Outside Diameter	7.087 Inch 180 Millimeter
Outer Race Width	1.614 Inch 41 Millimeter
d1 ≈	114.55 mm
D2 ≈	155.4 mm
r1,2 min.	3 mm

da min.	99 mm
da max.	114.9 mm
Da max.	166 mm
ra max.	2.5 mm
Basic dynamic load rating C	140 kN
Basic static load rating C0	96.5 kN
Fatigue load limit Pu	3.55 kN
Calculation factor kr	0.03
Calculation factor f0	13.3
Mass bearing	4.29 kg