

FBJ M804048/M804010 tapered roller bearings

FBJ M804048/M804010 tapered roller bearings, Units and Housings CAD models , 160.338 mm da Manufacturing Service . Get Your 121.818 mm Ca Free.

da	160.338 mm
Da	319.999 mm
Ca	121.818 mm
A1	180.975 mm
A2	317.5 mm
S	4.763 mm
ba	88.106 mm
H	377.825 mm
H1	190.5 mm
H2	76.2 mm
J min.	530.225 mm
J max.	600.075 mm
J1	117.475 mm
L	679.45 mm
N1	28.575 mm
R1	114.3 mm
R2	41.275 mm
RG	3/4 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SAW 536
Bearing	23236 CCK/W33

Adapter sleeve assembly	SNW 136×6.5/16
Stabilizing ring	SR-36-30
Taconite seal	TER 146
End plug (suffix Y)	EPR 19
Max. speed for Taconite seal	460 r/min
P60°	234 kN
P90°	140 kN
P120°	84.5 kN
P150°	75.6 kN
P180°	89 kN
Pa	60.5 kN
Mass pillow block	144 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	1304.1 g