

Fersa 30205F tapered roller bearings

LET OUR Fersa 30205F tapered roller bearings EXPERTS GET YOU 63.5 mm da THE PARTS YOU NEED.

da	63.5 mm
Da	130 mm
Ca	37.008 mm
A1	79.375 mm
A2	195.262 mm
S	3.175 mm
ba	32.544 mm
H	161.925 mm
H1	82.55 mm
H2	30.163 mm
J min.	219.075 mm
J max.	244.475 mm
J1	47.625 mm
L	285.75 mm
N1	19.05 mm
R1	46.038 mm
R2	21.431 mm
RG	1/4 NPT
PG	1/8 NPT
h	28.575 mm
Housing	SAFS 515
Bearing	22215 EK
Adapter sleeve assembly	SNW 15×2.1/2

Stabilizing ring	SR-15-0
Taconite seal	TER 38
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
P60°	104 kN
P90°	59.6 kN
P120°	36.9 kN
P150°	33.4 kN
P180°	40 kN
Pa	6.94 kN
Mass pillow block	15.4 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	68.04 g