

# Fersa 33008F tapered roller bearings

What are the types of Fersa 33008F tapered roller bearings 47 Outer Diameter (mm) ? 20x47x17.8 Size (mm) Manufacturing Service . Get Your Free, Instant price, design review.

Size (mm)	20x47x17.8
Bore Diameter (mm)	20
Outer Diameter (mm)	47
Width (mm)	17,8
D	47 mm
d	20 mm
C	17.8 mm
B	18 mm
D1	33 mm
F	25 mm
r1,2 – min.	1 mm
r3,4 – min.	0.3 mm
Basic dynamic load rating – C	16.1 kN
Basic static load rating – C0	18 kN
Fatigue load limit – Pu	2.2 kN
Maximum dynamic radial loads – Fr	17.6 kN
Maximum static radial loads – F0r	25.5 kN
Limiting speed	4000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.18

EAN	7316570998849
Product Group	B04144
Roller Surface Profile	Flat
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Needle Bearing
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Caged   With Inner Ring   Lip Seal
Long Description	20MM Bore; 47MM Roller Diameter; 17.8MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing
UNSPSC	31171530
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NA 2204.2RSX
Weight / LBS	0.397
Bore	0.787 Inch   20 Millimeter
Roller Diameter	1.85 Inch   47 Millimeter
Roller Width	0.701 Inch   17.8 Millimeter
r1,2 min.	1 mm
r3,4 min.	0.3 mm
Basic dynamic load rating C	16.1 kN
Basic static load rating C0	18 kN
Fatigue load limit Pu	2.16 kN

Maximum dynamic radial load $F_{r \max}$ .	17.6 kN
Maximum static radial load $F_{0r \max}$ .	25.5 kN
Mass support roller	0.18 kg