

# Fersa 332/32F tapered roller bearings

LET OUR Fersa 332/32F tapered roller bearings EXPERTS GET 36 mm A YOU THE PARTS 21 mm A1 YOU NEED.

|   |          |
|---|----------|
| A   | 36 mm    |
| A1  | 21 mm    |
| B   | 27 mm    |
| d   | 23.81 mm |
| Dz  | 60 mm    |
| E   | 12.5 mm  |
| G   | R1/8"    |
| H   | 36.5 mm  |
| H1  | 10 mm    |
| H2  | 70 mm    |
| J   | 50.8 mm  |
| L   | 70 mm    |
| L1  | 21 mm    |
| N   | M10      |
| s1  | 13.5 mm  |
| S   | 7.5 mm   |
| Z   | 47.3 mm  |
| C   | 14 kN    |
| C0  | 7.88 kN  |
| T min.                                      | -20 °C   |
| T max.                                      | 100 °C   |
| Weight                                      | 0.65 kg  |
| Recommended tightening torque for set screw | 3.7 Nm   |

|                                 |            |
|---------------------------------|------------|
| Designation of housing          | PAE205N-   |
| Designation of bearing          | US205-15G2 |
| Designation of closed end cover | SCC205     |
| Designation of open end cover   | SCOU205-15 |