

# Fersa 387S/382 tapered roller bearings

The online Fersa 387S/382 tapered roller bearings 130 mm da parts 125.412 mm dc store gives you immediate access to a selection of more than 1.4 million new, used, remanufactured.

da	130 mm
db	149.225 mm
dc	125.412 mm
Da	230 mm
Ca	73.787 mm
A1	130.175 mm
A2	203.2 mm
S	4.763 mm
ba	57.944 mm
H	292.1 mm
H1	152.4 mm
H2	60.325 mm
L	466.725 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	59.531 mm
Housing	SSAFS 226
Bearing	22226 E
Lock nut	AN 26
Lock washer	W 26

Stabilizing ring	SR-26-0
Labyrinth ring (db shaft position)	LOR 136
Labyrinth ring (dc shaft position)	LOR 122
End plug (suffix Y)	EPR 27
Bearing limiting speed	3600 r/min
P60°	308 kN
P90°	185 kN
P120°	125 kN
P150°	118 kN
P180°	151 kN
Pa	98.3 kN
Mass pillow block	81.2 kg
Cap bolt	3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Eye bolt	3/8-16 UNC
Initial grease fill	765.45 g