

Fersa 62207 deep groove ball bearings

Our highly-skilled and factory-trained service experts 0.0 Inventory have the resources to help you with all your Fersa 62207 deep groove ball bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

| | |
|--------------------------|---------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| EAN | 0883450507028 |
| Weight / US pound | 0.01 |
| Product Group | M06110 |
| Shaft Size | 2.559 in |
| Shaft Size Type | Metric |
| Weight | 19 lb |
| UPC Code | 0883450507028 |
| Type E Open Cover Number | EUDR-2 1/4 |
| Dimension B | 4 in |
| Dimension L | 6-7/8 in |
| Dimension A | 3-9/16 in |
| Dimension J | 5-3/8 in |
| Dimension A2 | 3/16 in |
| Bolt Diameter | 5/8 in |
| Dimension A1 | 1-1/2 in |
| Dimension D 1 | 5-5/16 in |
| Dimension d1 | 4-1/16 in |

| | |
|--|---|
| Dimension Ac | 4.7375 in |
| Dimension d2 | 4.945 in |
| e | 0.40 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 2.17 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 2.63 |
| K Factor | 1.51 |
| C90 Dynamic Load Rating ² | 11600 lb |
| C0 Static Load Rating | 54000 lb |
| Fa-max Maximum Permissible Thrust Load ³ | 3454 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ⁴ | 9500 lb |
| Max. Speed ⁵ | 2420 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |