

Fersa F-15127 tapered roller bearings

Can't find what you're looking for Fersa F-15127 tapered roller bearings ? Our expert 252.412 mm da Representatives be in contact with you shortly!

da	252.412 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	379.425 mm
ba	100.806 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
L	869.95 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	73.025 mm
Housing	SSAFS 056 KAUB
Bearing	23056 CCK/W33
Adapter sleeve assembly	SNP 3056×9.15/16
Stabilizing ring	2 x A8819
Taconite seal	2 x TER 607
End plug (suffix Y)	X-5217-2
Max. speed for Taconite seal	310 r/min

P60°	669 kN
P90°	400 kN
P120°	249 kN
P150°	222 kN
P180°	267 kN
Pa	89 kN
Mass pillow block	316 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Initial grease fill	3515.4 g