

FLCTE20 INA Relubricatable No Bearing units

| | |
|------------------------------------|--------------------------|
| Bearing number | FLCTE20 |
| Brand | INA |
| Bore Diameter (mm) | 20 |
| d | 20 mm |
| U | 33 mm |
| d3 | 33 mm |
| A1 | 17 mm |
| B1 | 31 mm |
| H | 90.5 mm |
| J | 71.4 mm |
| L | 66.5 mm |
| N | 9 mm |
| A2 | 9.5 mm |
| Weight | 0.39 Kg |
| Basic dynamic load rating (C) | 12.8 kN |
| Nominal Bolt Circle Diameter Round | 2.8 Inch 71 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Category | Flange Block Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.39 |
| EAN | 4012802791532 |
| Product Group – BDI | M06110 |

| | |
|---------------------------|---|
| Number of Mounting Holes | 2 |
| Mounting Method | Eccentric Collar |
| Housing Style | 2 Bolt Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 9 Millimeter |
| Relubricatable | No |
| Insert Part Number | RAE20NPPB |
| Seals | Double Lip Contact |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Metric |
| Long Description | 2 Bolt Flange Block; 20MM Bore; 71MM Bolt Circle; 71.4MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 31MM Length Thru Bore; No Relubricatable; Double Lip Contact Seals |
| Other Features | Single Row Small Center Bolt With Set Screw |
| Category – BDI | Flange Block |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | FLCTE20 |
| Weight / LBS | 0.86 |

| | |
|-----------------------|------------------------------|
| Length Thru Bore | 1.22 Inch 31 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Bore | 0.787 Inch 20 Millimeter |
| Bolt Spacing | 2.811 Inch 71.4 Millimeter |