

FLT CBK-337 tapered roller bearings

How do I place an EMERGENCY 82.55×133.35×39.688 Size (mm) order for a FLT CBK-337 tapered roller bearings that I want to pick up 133,35 Outer Diameter (mm) at a our store?

| | |
|---------------------------------|---------------------|
| Size (mm) | 82.55×133.35×39.688 |
| Bore Diameter (mm) | 82,55 |
| Outer Diameter (mm) | 133,35 |
| Width (mm) | 39,688 |
| d | 82,55 mm |
| D | 133,35 mm |
| T | 39,688 mm |
| B | 39,688 mm |
| C | 32,545 mm |
| d1 | 110.5 mm |
| a | 32.19 mm |
| e | 0.4 |
| Y2 | 1.49 |
| Y0 | 0.82 |
| Mass | 2.18 kg |
| Dynamic load, C | 177 kN |
| Rating life coefficient, A2 | 1.4 |
| Static load, C0 | 305 kN |
| Fatigue limit load, Cu | 36.4 kN |
| Nlim (oil) | 3,500 rpm |
| Nlim (grease) | 2,600 rpm |
| Min operating temperature, Tmin | -40 °C |

| | |
|---|----------|
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.45 Hz |
| Characteristic rolling element frequency, BSF | 10.09 Hz |
| Characteristic outer ring frequency, BPF0 | 11.31 Hz |
| Characteristic inner ring frequency, BRFI | 13.69 Hz |
| ra max | 3.5 mm |
| rla max | 3.3 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 2.147 |
| Product Group | B04334 |