

FYH UCT209-28E bearing units

YOU'LL 90 Bore Diameter (mm) FIND 90x115x13 Size (mm) AN EXTENSIVE SELECTION OF FYH UCT209-28E bearing units FOR SALE.

Size (mm)	90x115x13
Bore Diameter (mm)	90
Outer Diameter (mm)	115
Width (mm)	13
d	90 mm
D	115 mm
B	13 mm
C	13 mm
r min.	1 mm
da min.	95 mm
da max	96 mm
Da max.	110 mm
ra max.	1 mm
Weight	0,285 Kg
Basic dynamic load rating (C)	19 kN
Basic static load rating (C0)	19,7 kN
(Grease) Lubrication Speed	5 400 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.272
EAN	4547359586213
Product Group	B00308
Enclosure	2 Seals

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	90MM Bore; 115MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.6
Outside Diameter	4.528 Inch 115 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Bore	3.543 Inch 90 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	90 mm
static load capacity:	19700 N
outside diameter:	115 mm
precision rating:	ISO Class 0
overall width:	13 mm
finish/coating:	Uncoated

bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	13 mm
snap ring included:	Without Snap Ring
outer ring width:	13 mm
internal clearance:	CN
maximum rpm (grease):	5400 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1 mm
dynamic load capacity:	19000 N
manufacturer product page:	Click here