

# FYH UCTH209-27-300 bearing units

What are the types of FYH UCTH209-27-300 bearing units ?  
Manufacturing Service . Get Your Free, Instant N/A Minimum Buy  
Quantity price, design 0.0 Inventory review.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 13.154   |
| EAN                       | 0662327112677  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215LBC3  |
| Seals                     | Multi Labyrinth  |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 2 Bolt Pillow Block; 2-7/16" Bore; 3-1/4" Base to Center Height; Adapter Sleeve Mount; Sph |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | PELB6839R                      |
| Manufacturer Internal Number  | 5811267                        |
| Weight / LBS                  | 27                             |
| Bolt Spacing Maximum          | 9.625 Inch   244.475Millimeter |
| Nominal Bolt Center to Center | 9.1 Inch   232 Millimeter      |
| Bolt Spacing Minimum          | 8.625 Inch   219.075Millimeter |
| B                             | 3.25 Inch   82.55 Millimeter   |
| D                             | 0 Inch   0 Millimeter          |
| d                             | 2.438 Inch   61.925 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |