

Gamet 126088X/ 126136X tapered roller bearings

What are the dimensions 200 mm d of a Gamet 126088X/ 126136X tapered roller bearings? Manufacturing 310 mm D Service . Get Your Free, Instant Quote

| | |
|------------------------------------|-----------|
| d | 200 mm |
| D | 310 mm |
| B | 82 mm |
| D1 | 282.3 mm |
| rs min | 2.1 mm |
| Number of lubrication holes | 3 |
| b | 14.3 mm |
| k | 7 mm |
| e | 0.23 |
| Y1 | 2.95 |
| Y2 | 4.4 |
| Y0 | 2.89 |
| Radial clearance class | CN |
| Mass | 24.1 kg |
| Dynamic load, C | 1,310 kN |
| Static load, C0 | 1,790 kN |
| Fatigue limit load, Cu | 135 kN |
| Nref | 1,800 rpm |
| Nlim | 2,300 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 200 °C |
| Characteristic cage frequency, FTF | 0.44 Hz |

| | |
|---|----------|
| Characteristic rolling element frequency, BSF | 8.37 Hz |
| Characteristic outer ring frequency, BPF0 | 10.6 Hz |
| Characteristic inner ring frequency, BRFI | 13.4 Hz |
| da min | 210.2 mm |
| Da max | 299.8 mm |
| ra max | 2 mm |