

Gamet 181115/181200XP tapered roller bearings

What is the best place to buy Gamet 181115/181200XP tapered roller bearings 250x180x42 Size (mm) online? Manufacturing Service .

Size (mm)	250x180x42
Bore Diameter (mm)	250
Outer Diameter (mm)	180
Width (mm)	42
d	180 mm
D	250 mm
B	42 mm
d1	203 mm
D1	223 mm
E	232 mm
s	2.5 mm
r1,2 – min.	2 mm
r3,4 – min.	1.1 mm
da – min.	189 mm
das	199 mm
Da – max.	241 mm
Db – max.	243 mm
ra – max.	2 mm
rb – max.	1 mm
Basic dynamic load rating – C	391 kN
Basic static load rating – C0	695 kN
Fatigue load limit – Pu	75 kN

Reference speed	1100 r/min
Limiting speed	1400 r/min
Calculation factor – kr	0.2
Calculation factor – e	0.3
Calculation factor – Y	0.4
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	6.446
EAN	7316572319499
Product Group	B04144
Bore Profile	Straight
Cage Material	None
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	No
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Full Complement 2 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring

Long Description	180MM Bore; Straight Bore Profile; 250MM Outside Diameter; 42MM Width; RBEC 1 ISO P0; Single Row;
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NCF 2936 CV
Weight / LBS	14.198
Width	1.654 Inch 42 Millimeter
Outside Diameter	9.843 Inch 250 Millimeter
Bore	7.087 Inch 180 Millimeter
d1 ≈	203 mm
D1 ≈	223 mm
s max.	2.5 mm
r1,2 min.	2 mm
r3,4 min.	1.1 mm
da min.	189 mm
Da max.	241 mm
Db max.	243 mm
ra max.	2 mm
rb max.	1 mm
Basic dynamic load rating C	391 kN
Basic static load rating C0	695 kN
Fatigue load limit Pu	75 kN
Calculation factor kr	0.2
Calculation factor e	0.3
Calculation factor Y	0.4
Mass bearing	6.14 kg