

# Gamet 70030/70062 tapered roller bearings

Welcome to the Gamet 70030/70062 tapered roller bearings 52.375 mm dc online 55 mm da seller. 65.075 mm db

da	55 mm
db	65.075 mm
dc	52.375 mm
Da	120 mm
Ca	52.807 mm
A1	79.375 mm
A2	196.85 mm
ba	29.369 mm
H	157.162 mm
H1	82.55 mm
H2	30.163 mm
J min.	206.375 mm
J max.	241.3 mm
J1	50.8 mm
L	279.4 mm
N1	15.875 mm
R1	44.45 mm
R2	25.4 mm
RG	1/8 NPT
PG	1/8 NPT
h	38.1 mm
Housing	FSAF 311
Bearing	1311 ETN9

Lock nut	AN 20
Lock washer	W 11
Stabilizing ring	2 x SR-1611
Taconite seal (db shaft position)	TER 40
Taconite seal (dc shaft position)	TER 27
End plug (suffix Y)	EPR 6
Max. speed for Taconite seal	1200 r/min
P60°	35.6 kN
P90°	21.4 kN
P120°	13.3 kN
P150°	12 kN
P180°	14.2 kN
Pa	9.34 kN
Mass pillow block	11.4 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.5 in
Initial grease fill	68.04 g