

# Gamet 85050/85090C tapered roller bearings

We Provide Extensive Gamet 85050/85090C tapered roller bearings Selection 0.0 Inventory N/A Minimum Buy Quantity And Competitive REXNORD Manufacturer Name Wholesale Pricing.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 27.24  |
| EAN                       | 0698210706005  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 2400U  |
| Seals                     | Light Contact  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Collar   With Set Screw  |
| Long Description          | 4 Bolt Pillow Block; 4" Bore; 4-1/4" Base to Center Height; Concentric Collar Mount; Spher |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | KEP2400F                        |
| Manufacturer Internal Number  | 6870600                         |
| Weight / LBS                  | 60                              |
| D                             | 5.188 Inch   131.775 Millimeter |
| Bolt Spacing Minimum          | 12 Inch   304.8Millimeter       |
| d                             | 4 Inch   101.6 Millimeter       |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| Nominal Bolt Center to Center | 12.1 Inch   308.5 Millimeter    |
| Bolt Spacing Maximum          | 13 Inch   330.2Millimeter       |
| B                             | 4.25 Inch   107.95 Millimeter   |