

GLCTE17 INA Cartridge Pilot Diameter 0 Inch | 0 Millimeter Bearing units

| | |
|----------------------------------|-----------------------|
| Bearing number | GLCTE17 |
| Brand | INA |
| Bore Diameter (mm) | 17 |
| d | 17 mm |
| U | 30.5 mm |
| Thread (Q) | M6 |
| d3 | 28 mm |
| A1 | 15 mm |
| B1 | 28.6 mm |
| H | 81 mm |
| J | 63.5 mm |
| L | 58.7 mm |
| N | 6.6 mm |
| A2 | 8.4 mm |
| Weight | 0.3 Kg |
| Basic dynamic load rating (C) | 9.8 kN |
| Category | Flange Block Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.3 |
| Product Group – BDI | M06110 |
| Number of Mounting Holes | 2 |

| | |
|---------------------------|--|
| Mounting Method | Eccentric Collar |
| Housing Style | 2 Bolt Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 6.6 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | GRAE17NPPB |
| Seals | Double Lip Contact |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Metric |
| Long Description | 2 Bolt Flange Block; 17MM Bore; 64MM Bolt Circle; 63.5MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 28.6MM Length Thru Bore; Relubricatable; Double Lip Contact Seals |
| Other Features | Single Row Small Center Bolt With Set Screw |
| Category – BDI | Flange Block |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | GLCTE17 |
| Weight / LBS | 0.661 |
| Bore | 0.669 Inch 17 Millimeter |

| | |
|---------------------------------------|------------------------------|
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Length Thru Bore | 1.126 Inch 28.6 Millimeter |
| Bolt Spacing | 2.5 Inch 63.5 Millimeter |
| Nominal Bolt Circle Diameter Round | 2.5 Inch 64 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |