

GLCTE20 INA Relubricatable Yes Bearing units

Bearing number	GLCTE20
Brand	INA
Bore Diameter (mm)	20
d	20 mm
U	33 mm
Thread (Q)	M6
d3	33 mm
A1	17 mm
B1	31 mm
H	90.5 mm
J	71.4 mm
L	66.5 mm
N	9 mm
A2	9.5 mm
Weight	0.39 Kg
Basic dynamic load rating (C)	12.8 kN
Category	Flange Block Bearings
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.39
EAN	4012802791877
Product Group – BDI	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar

Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	9 Millimeter
Relubricatable	Yes
Insert Part Number	GRAE20NPPB
Seals	Double Lip Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Metric
Long Description	2 Bolt Flange Block; 20MM Bore; 71MM Bolt Circle; 71.4MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 31MM Length Thru Bore; Relubricatable; Double Lip Contact Seals
Other Features	Single Row Small Center Bolt With Set Screw
Category – BDI	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.ina.com
Manufacturer Item Number	GLCTE20
Weight / LBS	0.86
Bore	0.787 Inch 20 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter

Length Thru Bore	1.22 Inch 31 Millimeter
Nominal Bolt Circle Diameter Round	2.8 Inch 71 Millimeter
Bolt Spacing	2.811 Inch 71.4 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter