

# IKO BAM 59 needle roller bearings

YOU'LL FIND AN EXTENSIVE SELECTION OF 0.0 Inventory IKO BAM 59 needle roller bearings FOR SALE.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	14.103
EAN	7316576663505
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Tapered Adapter Sleeve
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22311 EK
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row   Heavy Duty
Long Description	4 Bolt Pillow Block; 1-15/16" Bore; 3-1/4" Base to Center Height; Tapered Adapter Sleeve M
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	FSAF 22611
Weight / LBS	29
B	3.25 Inch   82.55 Millimeter
Bolt Spacing Minimum	8.125 Inch   206.375Millimeter
d	1.938 Inch   49.225 Millimeter
Nominal Bolt Center to Center	8.8 Inch   223 Millimeter
D	4.875 Inch   123.83 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
Bolt Spacing Maximum	9.5 Inch   241.3Millimeter
mounting:	Four-Bolt Base
series:	FSAF
housing material:	Cast Iron
da	49.212 mm
Da	120 mm
Ca	52.807 mm
A1	79.375 mm
A2	123.825 mm
S	4.763 mm
ba	36.513 mm
H	157.162 mm
H1	82.55 mm
H2	30.163 mm
J min.	206.375 mm
J max.	241.3 mm
J1	50.8 mm

L	279.4 mm
N1	15.875 mm
R1	44.45 mm
R2	25.4 mm
RG	1/4 NPT
PG	1/8 NPT
h	36.513 mm
Housing	FSAF 611
Bearing	22311 EK
Adapter sleeve assembly	SNW 111×1.15/16
Stabilizing ring	SR-13-11
Labyrinth ring	2 x LER 24
End plug (suffix Y)	EPR 5
Bearing limiting speed	5600 r/min
P60°	35.6 kN
P90°	21.4 kN
P120°	13.3 kN
P150°	12 kN
P180°	14.2 kN
Pa	6.94 kN
Mass pillow block	14.1 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.5 in
Initial grease fill	68.04 g