

# IKO BHA 2020 Z needle roller bearings

Find 40x62x12 Size (mm) the discount IKO BHA 2020 Z needle roller bearings online you need . We offer ... If you check 40 Bore Diameter (mm) out our large selection of IKO BHA 2020 Z needle roller bearings once .

Size (mm)	40x62x12
Bore Diameter (mm)	40
Outer Diameter (mm)	62
Width (mm)	12
d	40 mm
D	62 mm
B	12 mm
C	12 mm
r min.	0,6 mm
da min.	44 mm
da max	45 mm
Da max.	58 mm
ra max.	0,6 mm
Weight	0,11 Kg
Basic dynamic load rating (C)	12,2 kN
Basic static load rating (C0)	8,9 kN
(Grease) Lubrication Speed	11 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.109

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 62MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6908LLB/2AS
Weight / LBS	0.241
Bore	1.575 Inch   40 Millimeter
Outer Race Width	0.472 Inch   12 Millimeter
Outside Diameter	2.441 Inch   62 Millimeter
bore diameter:	40 mm
precision rating:	ISO Class 0
outside diameter:	62 mm
finish/coating:	Uncoated
overall width:	12 mm
bearing material:	High Carbon Chrome Steel

bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	12 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	12 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	11000 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	11000 RPM
dynamic load capacity:	12200 N
series:	69
static load capacity:	8900 N
manufacturer product page:	<a href="#">Click here</a>