

IKO BHAM 1112 needle roller bearings

What 95 Bore Diameter (mm) are the dimensions of a IKO BHAM 1112 needle roller bearings? Manufacturing 95x130x18 Size (mm) Service . Get Your Free, Instant Quote

Size (mm)	95x130x18
Bore Diameter (mm)	95
Outer Diameter (mm)	130
Width (mm)	18
d	95 mm
D	130 mm
B	18 mm
C	18 mm
r min.	1,1 mm
da min.	101,5 mm
da max	104 mm
Da max.	123,5 mm
ra max.	1 mm
Weight	0,579 Kg
Basic dynamic load rating (C)	33,5 kN
Basic static load rating (C0)	33,5 kN
Reference speed	2 800 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
EAN	0692314678954
Weight / US pound	1.285

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	95MM Bore; 130MM Outside Diameter; 18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricat
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.28
Bore	3.74 Inch 95 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	95 mm
precision rating:	ISO Class 0

outside diameter:	130 mm
finish/coating:	Uncoated
overall width:	18 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	18 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	18 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	2800 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	5700 RPM
dynamic load capacity:	33500 N
series:	69
static load capacity:	33500 N
manufacturer product page:	Click here