

IKO BR 142216 U needle roller bearings

High Quality IKO BR 142216 U needle roller bearings. Competitive Pricing. Accept Small Order. 150.813 mm da Easy and Fast Shipping.

da	150.813 mm
Da	259.999 mm
Ca	86.614 mm
A1	149.225 mm
A2	261.938 mm
ba	64.294 mm
H	305.594 mm
H1	152.4 mm
H2	60.325 mm
J min.	396.875 mm
J max.	441.325 mm
J1	85.725 mm
L	511.175 mm
N1	28.575 mm
R1	87.313 mm
R2	38.1 mm
RG	3/4 NPT
PG	1/4 NPT
h	43.656 mm
Housing	SAF 034 KA
Bearing	23034 CCK/W33
Adapter sleeve assembly	SNW 3034×5.15/16

Stabilizing ring	2 x SR-0-24
Taconite seal	TER 140
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	520 r/min
P60°	249 kN
P90°	149 kN
P120°	94.3 kN
P150°	85.9 kN
P180°	103 kN
Pa	34 kN
Mass pillow block	63.9 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	481.95 g