

IKO CRB 25025 UU thrust roller bearings

170 Million used N/A Minimum Buy Quantity IKO CRB 25025 UU thrust roller bearings SKF Manufacturer Name instantly searchable. Shop our large selection of parts 0.0 Inventory based on brand, price, description, and location. Order the with stock ...

| | |
|---------------------------|--------------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 65.83 |
| EAN | 7316576668654 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Shaft Mount |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 7/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22322 CC/W33 |
| Seals | Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Metric |
| Other Features | Double Row Heavy Duty |

| | |
|-------------------------------|---|
| Long Description | 2 Bolt Pillow Block; 110MM Bore; 152.4MM Base to Center Height; Shaft Mount Mount; Spherical Roller |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | SAF 22322 |
| Weight / LBS | 145 |
| Bolt Spacing Maximum | 16 Inch 406.4Millimeter |
| D | 8.125 Inch 206.375 Millimeter |
| d | 4.331 Inch 110 Millimeter |
| Bolt Spacing Minimum | 14.625 Inch 371.475Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| B | 6 Inch 152.4 Millimeter |
| Nominal Bolt Center to Center | 15.3 Inch 389 Millimeter |
| da | 110 mm |
| db | 123.825 mm |
| dc | 106.375 mm |
| Da | 240 mm |
| Ca | 89.789 mm |
| A1 | 133.35 mm |
| A2 | 206.375 mm |
| S | 4.763 mm |
| ba | 63.5 mm |
| H | 287.337 mm |
| H1 | 152.4 mm |
| H2 | 60.325 mm |

| | |
|------------------------------------|-------------|
| J min. | 371.475 mm |
| J max. | 406.4 mm |
| J1 | 82.55 mm |
| L | 466.725 mm |
| N1 | 25.4 mm |
| R1 | 79.375 mm |
| R2 | 36.513 mm |
| RG | 1/2 NPT |
| PG | 1/4 NPT |
| h | 61.119 mm |
| Housing | SAF 322 |
| Bearing | 22322 E |
| Lock nut | AN 22 |
| Lock washer | W 22 |
| Stabilizing ring | SR-0-22 |
| Labyrinth ring (db shaft position) | LOR 121 |
| Labyrinth ring (dc shaft position) | LOR 113 |
| End plug (suffix Y) | EPR 14 |
| Bearing limiting speed | 2800 r/min |
| P60° | 189 kN |
| P90° | 113 kN |
| P120° | 73.8 kN |
| P150° | 68.1 kN |
| P180° | 84.5 kN |
| Pa | 54.7 kN |
| Mass pillow block | 65.8 kg |
| Cap bolt | 2 x 1-8 UNC |

| | |
|--|----------------|
| Cap bolt recommended tightening torque | 1220 N·m |
| Cap bolt, SAE grade | 8 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 0.875 in |
| Initial grease fill | 382.73 g |