

IKO CRBC 40040 thrust roller bearings

Advance IKO CRBC 40040 thrust roller bearings is your source for quality and accessories. 254 Outer Diameter (mm) shop online for home delivery or pick up in one 533.4x254x133.35 Size (mm) of our 10000 .

Size (mm)	533.4x254x133.35
Bore Diameter (mm)	533,4
Outer Diameter (mm)	254
Width (mm)	133,35
d	254 mm
D	533.4 mm
T	133.35 mm
d1	390 mm
B	120.65 mm
C	77.788 mm
r1,2 – min.	6.4 mm
r3,4 – min.	6.4 mm
a	164 mm
da – max.	300 mm
db – min.	286 mm
Da – min.	420 mm
Da – max.	502 mm
Db – min.	501 mm
Ca – min.	14 mm
Cb – min.	55 mm
ra – max.	6 mm

rb – max.	6 mm
Basic dynamic load rating – C	2090 kN
Basic static load rating – C0	2900 kN
Fatigue load limit – Pu	240 kN
Reference speed	800 r/min
Limiting speed	1100 r/min
Calculation factor – e	0.88
Calculation factor – Y	0.68
Calculation factor – Y0	0.4
d1 ≈	389.5 mm
r1,2 min.	6.4 mm
r3,4 min.	6.4 mm
da max.	300 mm
db min.	286 mm
Da min.	420 mm
Da max.	502 mm
Db min.	501 mm
Ca min.	8 mm
Cb min.	55 mm
ra max.	6 mm
rb max.	6 mm
Basic dynamic load rating C	2090 kN
Basic static load rating C0	2900 kN
Fatigue load limit Pu	240 kN
Calculation factor e	0.88
Calculation factor Y	0.68
Calculation factor Y0	0.4
Mass bearing	120 kg